CLAIMS

What is claimed is:

10

15

20

25

30

1. A method for requantizing coefficients of a bit stream, the method comprising:

receiving a plurality of input coefficients (F_i) quantized at an input quantization scale (q_i) , the input coefficients associated with the bit stream;

providing an output quantization scale (q_o) , wherein the output quantization scale is greater than the input quantization scale to allow for rate reduction of the bit stream; and

transmitting a plurality of output coefficients (F_o) quantized at the output quantization scale, wherein the plurality of output coefficients are determined using a formula minimizing the difference between dequantized input coefficients (f_i) and dequantized output coefficients (f_o).

- 2. The method of claim 1, wherein the quantized coefficients are DCT coefficients of an MPEG encoded bitstream.
- 3. The method of claim 1, wherein the plurality of input coefficients are associated with an intra macroblock or an inter macroblock.
- 4. The method of claim 1, wherein the output quantization scale has a larger step size than the input quantization scale.
 - 5. The method of claim 1, wherein input and output coefficients are dequantized using the following formula:

$$f = ((2F + k) \cdot q \cdot w)/32);$$

where k = 0 for intra macroblocks,

k = sign(F) for inter macroblocks,

"/" denotes integer division with truncation of the result toward zero,

w = weighting factor, and

sign(F) = -1, 0, or 1 if F < 0, F = 0, and F > 0 respectively.

- 6. The method of claim 1, wherein the formula minimizes requantization error.
- 7. The method of claim 6, wherein requantization error is minimized using the following formula:

$$q_{error} = \min[(2F_i + k_i) \cdot q_i \cdot w)/32 - (2F_o + k_o) \cdot q_o \cdot w)/32];$$

where k = 0 for intra macroblocks,

k = sign(F) for inter macroblocks,

"/" denotes integer division with truncation of the result toward zero,

w = weighting factor, and

subfix i and o in F, k and q represent input and output values respectively.

8. The method of claim 3, wherein output quantized coefficients associated with intra macroblocks are calculated using the following formula:

$$F_o = round(rF_i);$$

5

10

15

20

25

30

where r is equal to the input quantization scale divided by the output quantization scale and the round function rounds the result to the nearest integer.

- 9. The method of claim 8, wherein midpoints are rounded toward 0.
- 10. The method of claim 3, wherein output quantized coefficients associated with inter macroblocks are calculated using the following formula:

$$F_o = round \left(\frac{k_i}{2} \left[2r |F_i| + r - 1 \right] \right);$$

where r is equal to the input quantization scale divided by the output quantization scale and the round function rounds the result to the nearest integer.

- 11. The method of claim 10, wherein midpoints are rounded toward 0.
- 12. An apparatus for requantizing coefficients of a bit stream, the apparatus comprising:

an input interface configured to receive a plurality of input coefficients (F_i) quantized at an input quantization scale (q_i) , the input coefficients associated with the bit stream;

a processor configured to provide an output quantization scale (q_o) , wherein the output quantization scale is greater than the input quantization scale to allow for rate reduction of the bit stream; and

an output interface configured to transmit a plurality of output coefficients (F_o) quantized at the output quantization scale, wherein the plurality of output coefficients are determined using a formula minimizing the difference between dequantized input coefficients (f_o) and dequantized output coefficients (f_o) .

13. The apparatus of claim 12, wherein the quantized coefficients are DCT coefficients of an MPEG encoded bitstream.

- 14. The apparatus of claim 12, wherein the plurality of input coefficients are associated with an intra macroblock or an inter macroblock.
- 15. The apparatus of claim 12, wherein the output quantization scale has a larger step size than the input quantization scale.
- 16. The apparatus of claim 12, wherein input and output coefficients are dequantized using the following formula:

$$f = ((2F + k) \cdot q \cdot w)/32);$$

5

10

20

25

30

where k = 0 for intra macroblocks,

k = sign(F) for inter macroblocks,

"/" denotes integer division with truncation of the result toward zero,

w = weighting factor, and

sign(F) = -1, 0, or 1 if F < 0, F = 0, and F > 0 respectively.

- 17. The apparatus of claim 12, wherein the formula minimizes requantization error.
- 18. The apparatus of claim 17, wherein requantization error is minimized using the following formula:

$$q_{error} = \min[(2F_i + k_i) \cdot q_i \cdot w)/32 - (2F_o + k_o) \cdot q_o \cdot w)/32];$$

where k = 0 for intra macroblocks,

k = sign(F) for inter macroblocks,

"/" denotes integer division with truncation of the result toward zero,

w = weighting factor, and

subfix i and o in F, k and q represent input and output values respectively.

19. The apparatus of claim 14, wherein output quantized coefficients associated with intra macroblocks are calculated using the following formula:

$$F_o = round(rF_i);$$

where r is equal to the input quantization scale divided by the output quantization scale and the round function rounds the result to the nearest integer.

- 20. The apparatus of claim 19, wherein midpoints are rounded toward 0.
- 21. The apparatus of claim 14, wherein output quantized coefficients associated with inter macroblocks are calculated using the following formula:

$$F_o = round\left(\frac{k_i}{2}[2r|F_i| + r - 1]\right);$$

where r is equal to the input quantization scale divided by the output quantization scale and the round function rounds the result to the nearest integer.

- 22. The apparatus of claim 21, wherein midpoints are rounded toward 0.
- 23. A computer readable medium comprising computer code for requantizing coefficients of a bit stream, the computer readable medium comprising:

computer code for receiving a plurality of input coefficients (F_i) quantized at an input quantization scale (q_i) , the input coefficients associated with the bit stream;

computer code for providing an output quantization scale (q_o) , wherein the output quantization scale is greater than the input quantization scale to allow for rate reduction of the bit stream; and

computer code for transmitting a plurality of output coefficients (F_o) quantized at the output quantization scale, wherein the plurality of output coefficients are determined using a formula minimizing the difference between dequantized input coefficients (f_i) and dequantized output coefficients (f_o) .

24. The computer readable medium of claim 23, wherein input and output coefficients are dequantized using the following formula:

$$f = ((2F + k) \cdot q \cdot w)/32);$$

5

10

15

20

30

where k = 0 for intra macroblocks,

k = sign(F) for inter macroblocks,

"/" denotes integer division with truncation of the result toward zero,

w = weighting factor, and

$$sign(F) = -1$$
, 0, or 1 if $F < 0$, $F = 0$, and $F > 0$ respectively.

- 25. The computer readable medium of claim 23, wherein the formula minimizes requantization error.
- 26. The computer readable medium of claim 25, wherein requantization error is minimized using the following formula:

$$q_{error} = \min[(2F_i + k_i) \cdot q_i \cdot w)/32 - (2F_o + k_o) \cdot q_o \cdot w)/32];$$

where k = 0 for intra macroblocks,

k = sign(F) for inter macroblocks,

"/" denotes integer division with truncation of the result toward zero,

w = weighting factor, and

subfix i and o in F, k and q represent input and output values respectively.

27. An apparatus for requantizing coefficients of a bit stream, the apparatus comprising:

means for receiving a plurality of input coefficients (F_i) quantized at an input quantization scale (q_i) , the input coefficients associated with the bit stream;

means for providing an output quantization scale (q_o) , wherein the output quantization scale is greater than the input quantization scale to allow for rate reduction of the bit stream; and

means for transmitting a plurality of output coefficients (F_o) quantized at the output quantization scale, wherein the plurality of output coefficients are determined using a formula minimizing the difference between dequantized input coefficients (f_o) and dequantized output coefficients (f_o) .

28. The apparatus of claim 27, wherein input and output coefficients are dequantized using the following formula:

$$f = ((2F + k) \cdot q \cdot w)/32);$$

5

10

15

20

25

30

where k = 0 for intra macroblocks,

k = sign(F) for inter macroblocks,

"/" denotes integer division with truncation of the result toward zero,

w = weighting factor, and

$$sign(F) = -1$$
, 0, or 1 if $F < 0$, $F = 0$, and $F > 0$ respectively.

- 29. The apparatus of claim 27, wherein the formula minimizes requantization error.
- 30. The apparatus of claim 29, wherein requantization error is minimized using the following formula:

$$q_{error} = \min[(2F_i + k_i) \cdot q_i \cdot w)/32 - (2F_o + k_o) \cdot q_o \cdot w)/32];$$

where k = 0 for intra macroblocks,

k = sign(F) for inter macroblocks,

"/" denotes integer division with truncation of the result toward zero,

w = weighting factor, and

subfix i and o in F, k and q represent input and output values respectively.

31. The apparatus of claim 3, wherein output quantized coefficients associated with intra macroblocks are calculated using the following formula:

 $F_o = round(rF_i);$

where r is equal to the input quantization scale divided by the output quantization scale and the round function rounds the result to the nearest integer.

5